

SCREW CONVEYOR REDUCERS ACCESSORIES

Output Shafts

Solid output shafts are tapered to fit CGUSM hollow bore on the adaptor side of the housing. They are available in standard CEMA shaft diameters and configurations.



Output Shafts	Part Number	Screw Diameter	Shaft Diameter
CGUSM2	2SC0515	6"-9"	1.50"
	2SC0520	9"-12"	2.00"
	2SC0524	12"-14"	2.44"
	2SC0530	12"-20"	3.00"
CGUSM3	3SC0515	9"	1.50"
	3SC0520	9"-12"	2.00"
	3SC0524	12"-14"	2.44"
	3SC0530	12"-20"	3.00"
CGUSM4	4SC0515	9"	1.50"
	4SC0520	9"-12"	2.00"
	4SC0524	12"-14"	2.44"
	4SC0530	12"-20"	3.00"
	4SC0534	18"-24"	3.44"
CGUSM5	5SC0520	9"-12"	2.00"
	5SC0524	12"-14"	2.44"
	5SC0530	12"-20"	3.00"
	5SC0534	18"-24"	3.44"
CGUSM6	6SC0524	12"-14"	2.44"
	6SC0530	12"-20"	3.00"
	6SC0534	18"-24"	3.44"

Screw Conveyor Adaptor Kits

An SCADK mounting adaptor kit provides all the components needed to prepare a CGUSM reducer for screw conveyor applications. Each kit consists of CEMA mounting adaptor, output shaft keeper plate, oil seal, key and mounting hardware.



Adaptor Kits	
Size	Part Number
2	2SCADK
3	3SCADK
4	4SCADK
5	5SCADK
6	6SCADK